

TEST REPORT

1. Applicant

Client Name : FEELUX Co. Ltd.
Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea
Date of Receipt : 20190129

2. Purpose of Report :

3. Test Standard / Item : LED / 190211 FN1 RD-24V

4. Test Period : 20190129 ~ 20190129

5. Test Environment

Ambient Temp. : (0 +- 3) °C
Relative Humidity : (0 +- 10) % RH

6. Test Result : Refer to the attachment

Test Item

Name of Product :

FEELUX

Model / Rating :

Model : FEELUX

Rating :

Confirmation	Test by JSY	Technical manager JSY
--------------	----------------	--------------------------

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This report cannot be reproduced, except in full.
This report is for reference only. It cannot replace the report by standard organization(s).

TEST RESULT

Report Number	Sample Name	Sample Number	Test Standard
	FEELUX		LED

Test Item	Unit	Result	Memo
Beam Distribution Test	-	See attachment	
ATHD	%	0.0	
CIE 1931 Cxy		0.6902, 0.3097	
Correlated Color Temperature	K	5306	
Ra	-	-39.35	
Power Factor	%	1.000	
Input Voltage	V	23.940	
Input Current	A	0.520	
Input Watt	W	12.46	
Lamp Flux	lm	46.9	
Efficient	lm/W	3.77	
Illuminance	lx	14	1 m
		3	2 m
		2	3 m

* This test result is for the sample provided by the client.

Sample photo

Click to load image


Luminaire

Lamp

Report

No. of lamps	1	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt
Lamp flux (lm)	47	Operator	rrrent (A) 0.52
Total flux (lm)	47	Date	Power Factor 1

2019-02-11 오후 2:22:28



All luminous intensity values are in Cd/KLm unit.

Luminaire

Lamp

No. of lamps 1

Lamp flux (lm) 47

Total flux (lm) 47


Report

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt

Operator rrent (A) 0.52

Date Power Factor 1

2019-02-11 오후 2:22:28



All luminous intensity values are in Cd/KLm unit.

Luminaire

Lamp		Report	
No. of lamps	1	Filename: C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt	
Lamp flux (lm)	47	Operator	rrrent (A) 0.52
Total flux (lm)	47	Date	Power Factor 1

2019-02-11 오후 2:22:28

Luminous Intensity Data

GWC	0	30	60	90	120	150	180	210	240	270	300	330	360
0	13.52	13.38	13.73	12.66	13.23	12.49	13.52	13.38	13.73	12.66	13.23	12.49	13.52
10	13.10	12.90	12.25	12.74	12.47	12.42	13.09	13.31	12.97	12.60	12.80	13.12	13.10
20	13.90	13.07	12.04	11.86	12.33	12.33	12.45	12.73	12.62	11.88	12.00	13.14	13.90
30	12.63	11.79	10.30	11.20	11.15	10.98	11.69	11.55	12.40	11.28	11.21	11.60	12.63
40	11.51	11.55	8.59	9.29	10.51	10.04	9.33	9.86	11.15	9.60	9.96	11.15	11.51
50	10.18	9.42	6.90	8.54	7.90	8.38	8.10	7.99	9.70	7.99	7.80	9.30	10.18
60	8.65	8.34	5.03	6.00	6.42	6.48	5.89	6.69	7.96	5.54	6.33	7.36	8.65
70	6.64	6.49	3.24	4.12	4.21	4.10	4.20	4.87	5.82	3.13	4.66	5.69	6.64
80	4.00	4.19	2.03	1.35	1.83	2.87	2.34	2.96	4.24	1.62	2.47	3.73	4.00
90	2.86	2.01	0.84	0.40	1.39	1.43	2.26	1.41	1.77	-0.11	0.83	1.88	2.86
100	1.47	1.43	1.25	0.37	1.07	1.56	2.00	1.32	1.15	0.07	1.53	1.11	1.47
110	1.55	1.33	0.42	0.42	0.37	1.07	1.87	0.92	0.10	0.23	0.65	1.03	1.55
120	1.25	0.62	0.24	0.34	0.61	0.57	0.95	1.67	0.62	0.14	0.34	1.28	1.25
130	0.83	1.10	0.28	0.36	1.02	0.32	0.46	0.09	0.81	-0.51	0.23	0.10	0.83

Luminaire

Lamp		Report	
No. of lamps	1	Filename: C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt	
Lamp flux (lm)	47	Operator	rrrent (A) 0.52
Total flux (lm)	47	Date	Power Factor 1

2019-02-11 오후 2:22:28

Luminous Flux Table

Total Lamp Lumens: 46.9

Luminaire Efficiency (lm/W): 46.93

CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	0.31	0.31	0.67	0.67
10	2.44	2.75	5.87	5.86
20	4.69	7.45	15.88	15.87
30	6.29	13.73	29.28	29.26
40	7.19	20.92	44.61	44.58
50	7.15	28.07	59.84	59.81
60	6.38	34.44	73.44	73.40
70	4.90	39.35	83.89	83.84
80	3.02	42.37	90.34	90.28
90	1.55	43.92	93.64	93.59
100	1.29	45.21	96.39	96.33
110	0.85	46.06	98.21	98.15
120	0.68	46.74	99.67	99.61
130	0.18	46.93	100.06	100.00

Luminaire

Lamp

Report

No. of lamps 1

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt

Lamp flux (lm) 47



Operator rrent (A) 0.52

Total flux (lm) 47

Date Power Factor 1

2019-02-11 오후 2:22:28

IsoCandela (Type C)



Luminaire


Lamp

Report

No. of lamps	1	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt
Lamp flux (lm)	47	Operator	rrrent (A) 0.52
Total flux (lm)	47	Date	Power Factor 1

2019-02-11 오후 2:22:28

IsoLux Diagram (Ground)




Pole Height (m): 2.7

Area Width (m): 12

Luminaire

Lamp		Report	
No. of lamps	1	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt
Lamp flux (lm)	47	Operator	rrrent (A) 0.52
Total flux (lm)	47	Date	Power Factor 1
			2019-02-11 오후 2:22:28

IsoLux Diagram (Wall)



Pole Height (m): 2.7 Wall Distance (m): 2.7
Aiming Plane: 0 Wall Height (m): 12

Luminaire

Lamp

No. of lamps	1	Voltage (V)	23.94
Lamp flux (lm)	47	Current (A)	0.52
Total flux (lm)	47	Power Factor	1

Report

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt

Operator

Date

2019-02-11 오후 2:22:28

Illuminance Levels (Ground)

6.00	0.02	0.03	0.03	0.03	0.04	0.04	0.05	0.04	0.05	0.05	0.02	0.03	0.03
5.00	0.03	0.03	0.04	0.05	0.09	0.10	0.12	0.10	0.10	0.04	0.04	0.04	0.04
4.00	0.03	0.04	0.08	0.12	0.12	0.14	0.17	0.14	0.15	0.11	0.10	0.06	0.04
3.00	0.03	0.05	0.12	0.14	0.27	0.31	0.36	0.32	0.25	0.19	0.14	0.08	0.05
2.00	0.04	0.09	0.12	0.28	0.40	0.65	0.71	0.70	0.47	0.33	0.16	0.11	0.06
1.00	0.05	0.11	0.15	0.31	0.66	1.09	1.44	1.19	0.72	0.37	0.19	0.13	0.06
0.00	0.05	0.11	0.16	0.34	0.72	1.48	1.85	1.49	0.85	0.43	0.22	0.15	0.07
-1.00	0.05	0.11	0.15	0.30	0.62	1.13	1.42	1.09	0.64	0.32	0.19	0.13	0.06
-2.00	0.04	0.09	0.13	0.27	0.39	0.63	0.73	0.62	0.39	0.31	0.13	0.09	0.05
-3.00	0.04	0.05	0.11	0.14	0.31	0.33	0.34	0.30	0.27	0.14	0.13	0.07	0.04
-4.00	0.03	0.04	0.08	0.13	0.13	0.17	0.16	0.17	0.12	0.11	0.08	0.05	0.03
-5.00	0.03	0.03	0.05	0.07	0.10	0.11	0.11	0.12	0.09	0.04	0.03	0.03	0.03
-6.00	0.02	0.04	0.03	0.04	0.05	0.04	0.04	0.05	0.04	0.03	0.02	0.03	0.02
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.): 1.85

All illuminance level values are in lux.

Illum. (Min.): 0.02

Illum. Avg.: 0.23

Total Optical Solution Provider


<http://www.jnctech.co.kr>
J & C Technology Co., Ltd.


Luminaire

Lamp

No. of lamps	1	Report	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt
Lamp flux (lm)	47	Operator	rrrent (A)	0.52
Total flux (lm)	47	Date	Power Factor	1

2019-02-11 오후 2:22:28

Illuminance Cone Diagram



Luminaire

Lamp

No. of lamps	1	Voltage (V)	23.94
Lamp flux (lm)	47	Current (A)	0.52
Total flux (lm)	47	Power Factor	1

Report

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2018\190211 FN1 RD-24V.jdt

Operator

Date

2019-02-11 오후 2:22:28

Coefficient of Utilization

Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00