

TEST REPORT

1. Applicant

Client Name : FEELUX Co. Ltd.

Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea

Date of Receipt : 190319

2. Purpose of Report :

3. Test Standard / Item : LED / 190319 FN1 35K-24V 구형

4. Test Period : 190319 ~ 190319

5. Test Environment

Ambient Temp. : (0 +- 3) °C

Relative Humidity : (0 +- 10) % RH

6. Test Result : Refer to the attachment

Test Item

Name of Product :

FEELUX

Model / Rating :

Model : FEELUX

Rating :

Confirmation	Test by CGR	Technical manager CGR
--------------	----------------	--------------------------

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This report cannot be reproduced, except in full.

This report is for reference only. It cannot replace the report by standard organization(s).

TEST RESULT

Report Number	Sample Name	Sample Number	Test Standard
	FEELUX		LED

Test Item	Unit	Result	Memo
Beam Distribution Test	-	See attachment	
ATHD	%	0.0	
CIE 1931 Cxy		0.4343, 0.4151	
Correlated Color Temperature	K	3147	
Ra	-	80.32	
Power Factor	%	1.000	
Input Voltage	V	23.930	
Input Current	A	0.512	
Input Watt	W	12.26	
Lamp Flux	lm	614.9	
Efficient	lm/W	50.19	
Illuminance	lx	163	1 m
		41	2 m
		18	3 m

* This test result is for the sample provided by the client.


Sample photo

Click to load image

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02




All luminous intensity values are in Cd/KLm unit.

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02



All luminous intensity values are in Cd/Klm unit.

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02

Luminous Intensity Data

GWC	0	30	60	90	120	150	180	210	240	270	300	330	360
0	162.14	163.40	165.49	163.87	166.38	165.58	162.14	163.40	165.49	163.87	166.38	165.58	162.14
10	162.52	162.02	163.35	160.28	162.73	162.47	160.30	159.60	163.44	160.53	163.87	165.27	162.52
20	157.39	156.78	156.44	151.49	153.63	155.32	154.68	153.00	154.55	151.55	157.16	160.36	157.39
30	150.44	147.48	144.38	136.81	140.30	144.10	142.60	141.31	142.41	138.15	144.73	151.66	150.44
40	138.31	134.22	127.88	117.94	122.47	127.62	127.31	126.23	123.18	119.57	128.82	138.27	138.31
50	121.66	116.63	107.50	95.05	101.98	108.52	109.29	107.08	103.28	96.95	108.04	119.36	121.66
60	102.27	96.34	85.01	69.45	80.14	87.41	88.15	86.41	79.20	71.90	84.40	98.96	102.27
70	81.25	74.82	59.31	42.41	54.91	67.10	68.83	65.93	54.89	44.30	58.91	74.96	81.25
80	61.99	54.08	36.77	18.12	34.14	49.49	52.53	48.88	33.68	18.23	35.17	53.11	61.99
90	45.41	37.67	20.08	2.25	20.31	35.79	40.01	36.20	20.66	2.72	18.59	36.97	45.41
100	32.29	26.60	11.90	0.81	14.72	27.73	31.93	27.43	13.93	0.84	11.73	26.07	32.29
110	24.90	19.87	7.22	0.47	6.41	22.68	26.09	22.45	6.63	1.19	4.79	20.99	24.90
120	18.72	13.94	1.02	1.43	1.00	14.37	19.62	12.89	2.03	1.11	2.37	12.22	18.72
130	10.88	1.58	6.15	1.08	2.12	1.16	7.31	0.90	4.75	1.13	3.70	1.78	10.88

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02

Luminous Flux Table

Total Lamp Lumens: 615

Luminaire Efficiency (lm/W):614.89

CIE Classification: Direct


Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	3.93	3.93	0.64	0.64
10	30.85	34.78	5.66	5.66
20	58.13	92.92	15.11	15.11
30	78.69	171.61	27.91	27.91
40	89.87	261.47	42.52	42.52
50	90.56	352.04	57.25	57.25
60	81.38	433.42	70.49	70.49
70	64.12	497.54	80.91	80.92
80	44.60	542.14	88.17	88.17
90	28.90	571.04	92.87	92.87
100	20.31	591.35	96.17	96.17
110	14.04	605.39	98.45	98.45
120	7.96	613.35	99.75	99.75
130	1.54	614.89	100.00	100.00

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02

IsoCandela (Type C)




0 ~ 17	83 ~ 100
17 ~ 34	100 ~ 117
34 ~ 50	117 ~ 133
50 ~ 67	133 ~ 150
67 ~ 83	150 ~ 166

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02

IsoLux Diagram (Ground)




Pole Height (m): 2.7

Area Width (m): 12

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02



Pole Height (m): 2.7 Wall Distance (m): 2.7
Aiming Plane: 0 Wall Height (m): 12

Luminaire

Lamp

No. of lamps	1	Voltage (V)	23.93
Lamp flux (lm)	615	Current (A)	0.512
Total flux (lm)	615	Power Factor	1

Report

Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt
Operator	
Date	2019-03-19 오후 6:27:02

Illuminance Levels (Ground)

6.00	0.26	0.34	0.27	0.42	0.48	0.59	0.51	0.53	0.63	0.55	0.37	0.41	0.36
5.00	0.40	0.32	0.43	0.57	1.14	1.38	1.34	1.33	1.32	0.73	0.57	0.50	0.47
4.00	0.39	0.56	0.96	1.36	1.54	1.93	1.92	1.91	1.84	1.56	1.21	0.69	0.48
3.00	0.44	0.78	1.52	1.71	3.29	3.77	4.09	4.28	3.61	2.21	1.73	0.93	0.57
2.00	0.56	1.19	1.58	3.57	4.81	7.68	8.86	8.40	5.66	3.91	1.88	1.37	0.70
1.00	0.70	1.47	2.13	3.96	7.75	13.53	18.10	14.39	8.47	4.48	2.41	1.63	0.79
0.00	0.73	1.56	2.32	4.64	9.44	18.11	22.24	18.37	10.14	5.13	2.64	1.74	0.85
-1.00	0.69	1.47	2.13	4.09	7.95	13.80	18.13	13.78	8.18	4.26	2.42	1.64	0.81
-2.00	0.61	1.24	1.68	3.59	5.19	7.92	8.97	8.04	4.99	3.87	1.68	1.28	0.60
-3.00	0.50	0.79	1.55	1.96	3.46	4.00	4.17	3.94	3.36	1.79	1.67	0.88	0.47
-4.00	0.41	0.59	1.08	1.48	1.67	1.88	1.97	1.89	1.62	1.40	1.00	0.62	0.44
-5.00	0.41	0.43	0.52	0.68	1.22	1.32	1.37	1.35	1.20	0.59	0.45	0.34	0.44
-6.00	0.32	0.38	0.34	0.49	0.57	0.53	0.53	0.56	0.51	0.44	0.28	0.35	0.28
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.): 22.2

All illuminance level values are in lux.

Illum. (Min.): 0.26

Illum. Avg.: 2.83

Total Optical Solution Provider



<http://www.jnctech.co.kr>
J & C Technology Co., Ltd.

Luminaire

Lamp	Report			
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt		
Lamp flux (lm)	615	Operator	Current (A)	0.512
Total flux (lm)	615	Date	Power Factor	1

2019-03-19 오후 6:27:02

Illuminance Cone Diagram



Luminaire

Lamp

No. of lamps	1	Voltage (V)	23.93
Lamp flux (lm)	615	Current (A)	0.512
Total flux (lm)	615	Power Factor	1

Report

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190319 FN1 35K-24V 구형.jdt

Operator

Date

2019-03-19 오후 6:27:02

Coefficient of Utilization

Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00